THE MDF SPECIALIST





TRUPAN Ultralight

Offers a smooth and flawless surface with a consistent density profile.

Ideal for moulding and furniture making and interior design applications.



TRUPAN Ultralight is manufactured using pine fiber grown in ARAUCO's sustainably managed plantation forest. TRUPAN Ultralight has a homogeneous surface and excellent sanded finish. This panel offers a uniform color and consistent density profile. TRUPAN Ultralight combines an extremely light weight with excellent machining characteristics and physical mechanical properties, making it an ideal choice for furniture making and moulding manufacturing.

TRUPAN Ultralight

Applications

- Furniture
- Mouldings
- Picture frames
- Doors
- Lamination Substrate (low pressure)
- Display Fixtures
- CNC Spoilboards

Product Features

- · Extremely lightweight
- · Light, uniform color
- Consistent density profile
- Extra-smooth sanding
- · Lower tool wear
- · Reduced finished good transportation cost
- Available in thicknesses up to 50mm
- Made from 100% fresh pine fiber from sustainably-managed

Recommendations

- · Predrilling is required for inserting screws
- For product stability, painting or laminating both sides of the panel is recommended

Storage and Handling

• TRUPAN Ultralight should never be stored or used outdoors. The indoor storage area should be clean, dry, well-ventilated. and free of dust, dirt or particles that could contaminate the MDF. Store flat on bolsters on a level, hard surface. Constant relative humidity and temperature should be maintained. Before use, allow to stabilize to the same conditions as are expected after the panel is installed. Condition 48 to 72 hours prior to lamination.



TRUPAN ULTRALIGHT TECHNICAL INFORMATION							
Property	Density	Internal Bond	MOE	MOR	Edge Screw Pull	Face Screw Pull	Swelling 24h
Standard	EN 323 / ASTM 1037	EN 319 / ASTM 1037	EN 310 / ASTM 1037		EN 320 / ASTM 1037		EN 317 / ASTM 1037
Thickness in mm	kg/m³	kPa	N/mm ²	N/mm ²	N	N	%
12 - 14	470 - 550	520 - 600	1,800 - 2,200	22 - 28	-	-	<14
15 - 17	470 - 550	520 - 600	1,800 - 2,200	22 - 28	>650	>800	<12
18 - 24	470 - 550	520 - 600	1,800 - 2,200	22 - 28	>650	>800	<8
25 - 30	470 - 550	520 - 600	1,800 - 2,200	22 - 28	>650	>800	<10
38 - 45 - 50	470 - 550	520 - 600	1,800 - 2,200	22 - 28	>650	>800	<8

- · For panel sizes and other thicknesses, please contact panels@arauco.cl or your TRUPAN sales representative.
- . Formaldehyde emission classes available: Carb II, E1 and E2.
- For Certifications please download at www.trupan.com
- Thickness tolerance: -/+ 0.20 mm
- Length and width tolerance: -/+2mm
- Squareness tolerance: ≤3mm



QUALITY SUSTAINABILITY



ARAUCO

For more than 45 years, ARAUCO has been driven forward by its vision of being a global leader in the development of sustainable forest products, which has allowed us to become one of the largest and most respected forestry companies in the world.

ARAUCO's success is based on satisfying our customers with quality products and services while balancing the company's needs with those of our employees, the environment, and the people who live near our facilities and plantations. This is the starting point for the responsible and efficient management of our natural resources, the occupational health and safety of our workers and our active contribution to social development and welfare in the communities in which we operate.

All ARAUCO-branded products originate in sustainably managed plantation forests in Chile, Brazil, Argentina and Uruguay. No native forest wood or genetically modified trees are used to produce any ARAUCO product.

ARAUCO operates MDF mills in Argentina, Brazil, Canada, Chile and USA.

